


FULL-HEIGHT TURNSTILE BICYCLONE

Bicyclone turnstile barrier gate designed as a combination extended passage with regular single pedestrian entry point within one full height turnstile. Extended passage ensures smooth entry of bicycles, wheelchairs, large volume belongs and materials. Can be supplied both in fully welded or assembly (attractive for transportation) design.



MODEL OF THE FULL-HEIGHT TURNSTILE SERIES GUARANTEES FULL PROTECTION OF THE TERRITORY

 20
pers/min
CROSSING CAPACITY
(through the rotor)

 650 700
mm mm
PASSAGE WIDTH GATE WIDTH

 IP 41/54*
PROTECTIVE LEVEL

 MOTORIZED

 BI-DIRECTIONAL

Advantages

- Bi-directional
- Variety of metal and metal treatment types
- Three arms (angle between bars 120°) and four arms (angle between bars 90°) modifications
- Integration with any type of access control and ID systems
- Low power consumption
- Whisper quiet, low noise operation
- Possibility of customization
- Wide range of accessories
- Complete supply set as a standard
- Fail safe / fail secure

Standard

- 2 types of LED indication
- Hard Wired remote control
- Fail secure (with manual unlock by key)

Options

- Any access control systems upon request (e.g. passage counter, RFID/Proximity/BioMetric readers, coin acceptor, push button, barcode and QR-code reader)
- Heating function for external installation (for cold climates)
- Protective canopy or roof
- Fail-safe (automatic opening entrance, exit or both direction when power goes off)

* first figure is for indoor installation, second figure is for outdoor installation.
Protection level could be up to IP65 upon request.

Technical Specifications:

Unit width, mm	2300
Unit length, mm	1156
Unit high, mm	2290
Weight, kg (not more)	700
Standard mechanism - gate - rotor	Servo-drive (Motorized) Electro-mechanical
Available mechanism - rotor	Servo-drive (Motorized)

Controlled by:




access control system;



manual control

Electrical Specifications:

- Voltage:
 - from the AC (100-240)V, 50/60Hz;
 - from a DC source 12 V;
- Maximum power consumption 205W per pass




Materials

Standard housing	Brushed SS AISI 304
Available housing	Brushed SS AISI 316 Polished SS AISI 304 Polished SS AISI 316 Powder coated RAL

Installation areas:

- Governmental Institutions
- Military Bases
- Nuclear Power Plants
- Production sites (Industrial Plants)
- Commercial areas
- Financial institutions
- Airport Premises
- Business (Office) Centers
- Hotels
- Sport Complexes
- Recreation areas
- Urban areas
- Education Institutions
- others



** Protective canopy or roof available up on request