WALK THROUGH METAL DETECTOR
## CP-3180
18 Zones Standard

Features

- Eighteen mutual over-lapping detecting zones, Simultaneous alarm from multi- zones;

- Sensitivity adjustable: Each zone has 256 sensitivity level, 0-255 adjustable

- 5.7 inch LCD screen

- Infrared remote control

- Sound & LED alarm: Both Side LED indicator, easily show where the metal is.

- Automatically count passengers and alarm times

- Alarm strength indicator on control panel

- Password protection, only the authorized person can operate.

- Easy assembly: designed with only 2 pieces cables and 8 screws, simply-to-follow instruction.

- Harmless to human body: is harmless with heart pacemaker, pregnant women, magnetic floppy, recording tapes, etc.

- Using high density fireproof material

- Program Self-diagnostic when power on,no need initial or periodic calibration

- Modularization design,easy for maintenance and replacement.

- 4-8 hours backup battery (Option)

Specification

|	
Power Supply	AC85 V-264 V
Working temperature	-20°C --+50°C
Working Frequency	4KHZ—8KHZ
Standard External size	2200mm(H)X800mm(W)X580mm(D)
Standard Internal size	2010mm(H)X700mm(W)X500mm(D)
Package size for door panels	2260*650*260mm *1ctn
Package size for control unit	780*390*250 mm*1ctn
Gross weight	70KG

Application

Exhibition center

Bank

Electronic Factory

Prison

Government office

Hotel